## B(85T)X Cable Sleeves & Markers – Technical Data Sheet

### **Product Data**

### Storage:

Cool dry place out of direct sunlight

### Material:

PVC

#### **Operating Temperature:**

-20°C to +70°C

### **Application Method – Push On/Stretch On**

The MP Cable Sleeves and Sleeving is a high-grade thin wall PVC ideal for insulating wires where space is at a premium. Available in a variety of colours, this material is an economical solution that will meet your requirements. This product is ideal for cable or harness covering, with the push/stretch on application made easier with SEID's expanding tool.

- RoHS Compliant
- Economical
- Self-Extinguishing


**Eleven Colours** 



Property	Value	Test Method
Operating Temperature	-20°C to +70°C	BS 2848/3/85T
Flammability	Self-Extinguishing	
	in 30 Seconds	
Insulation Resistance	1010 Ohm/cm	
Dielectric Strength	20 kV/mm	
Tensile Strength	15MPa	
Elongation at Break	220%	
Hardness	BSS20-30	

# B(85T)X Cable Sleeves & Markers – Technical Data Sheet

## **Ordering Information**



## **Cut Sleeving**

Product Reference	Nominal Bore ID (mm)	Nominal Wall Thickness (mm)	Length	Colour	Form
B(85T)P05	0.5	0.4	Any length ± 0.5mm	YW = Yellow	Plain Cut Length
B(85T)P075	0.75	0.4		WE =White	Spiral Cut
B(85T)P10	1.0	0.4		BK = Black	Par-o-Cut
B(85T)P15	1.5	0.5		BN = Brown	Continuous
B(85T)P20	2.0	0.5		RD = Red	
B(85T)P25	2.5	0.5		OR = Orange	
B(85T)P50	5.0	0.5		GN = Green	
B(85T)P70	7.0	0.65		BE = Blue	
B(85T)P100	10.0	0.65		VT = Violet	
B(85T)P150	15.0	0.85		GY = Grey	
B(85T)P250	25.0	0.85		PK = Pink	

## **Printed Sleeving**

Product Reference*	Nominal Bore ID (mm)	Nominal Wall Thickness (mm)	Length	Colour	Form
B(85T)P05	0.5	0.4	Any length ± 1mm	YW = Yellow	Numeric
B(85T)P075	0.75	0.4	to accommodate	WE =White	Alpha-Numeric
B(85T)P10	1.0	0.4	marking	BK = Black	Alpha-Characters
B(85T)P15	1.5	0.5		BN = Brown	Instructions
B(85T)P20	2.0	0.5		RD = Red	Symbols
B(85T)P25	2.5	0.5		OR = Orange	Tables
B(85T)P50	5.0	0.5		GN = Green	Logos
B(85T)P70	7.0	0.65		BE = Blue	Single Line
B(85T)P100	10.0	0.65		VT = Violet	Multi Line
B(85T)P150	15.0	0.85		GY = Grey	Once Around
B(85T)P250	25.0	0.85		PK = Pink	Multiple around

### Please contact us for any sizes not listed......

Business Management Accreditations

Registered in England No. 412829